

## FF-12

## **Front Firing Powered Subwoofers**

<section-header></section-header>	(W) Width (D) Depth Height	
	(H) Height w/ feet	FF12 16-15/16" (430mm)
	(W) Width	14- 3/16" (360mm)
	(D) Depth w/ grille & amplifier	15-3/4" (400mm)
<text><image/><image/><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></text>	OBJECTIVE Earthquake's FF-12 subwoofer system was designed to offer consumers budget and volume optimized subwoofer system solutions. This unit scores high marks with custom home installers as it performs fantastically in front firing applications. With a small footprint, a variety of applications, and an incredible output; the FF12 is an "easy-to-use" subwoofer for both consumers and installers alike.	
SPECIAL FEATURES & HIGHLIGHTS		
<ul> <li>Front firing design with small footprint</li> <li>Single/slot front mounted port for optimized bass output</li> <li>Front mounted volume control with blue LED</li> <li>400-Watt class "A/B" high efficiency power amplifier</li> <li>24dB/Octave variable filter from 40 - 180Hz</li> <li>Automatic signal detection circuitry - automatically turns on the subwoofer ON/OFF</li> <li>Status LED indicators</li> <li>Low level (RCA) &amp; High level audio inputs</li> <li>Line through RCA &amp; High level audio outputs</li> <li>12" high power subwoofer</li> <li>0 - 180° phase shift</li> <li>40 - 180Hz crossover</li> </ul>	SPECIFICATIONS	
	FF-12	
	Amplifier Power	400 Watts
	Frequency Response	20 - 125Hz
	Weight	37 lbs
	Finish	Black Ash

