

Speaker Reference Chart

Model	Type	Continuous Power Input	Input Impedance	Freq. Response	Speaker Component	Efficiency (SPL)	Attenuators (Max. cut)	Finish	Grille	Connectors (incl. In/Out)	Other Features
-------	------	------------------------	-----------------	----------------	-------------------	------------------	------------------------	--------	--------	---------------------------	----------------

• SR (Z-Drive) Series Speakers

SR-F1B	2-Way Bass Reflex	360W(Low) 240W(High)	8Ω (low) 16 Ω(high)	70Hz-20kHz (AC-F1's use)	30cm, Compression HF Driver w/60°H x 40°V CD Horn	98dB		FRP, Gray	Removable Punched Metal, Black	Neutrik NL4MPR	APITON Plywood Cabinet
SR-L1B	Bass Reflex	450W×2	8Ω	35Hz-1kHz	Two 38cm, Bass Reflex Subwoofers w/ Double Magnets	96dB					
SR-F09	2-Way Bass Reflex	600W		70Hz-20kHz (AC-S09's Use)	30cm, Cone Speaker (90°H x 40°V) CD Horn w/Compression Driver	100dB		Plywood, black, paint	Steel plate, black, acrylic paint	Neutrik NL4MP × 2, M5 screw	
SR-F09-V1											
SR-F09-V2											
SR-F09-V3											
SR-L09	Bass Reflex	900W	4Ω	35Hz-1kHz	38cm, Cone Speaker × 2	96dB					
SR-L05		450W	8Ω	35Hz-1kHz	38cm, Cone Speaker	93dB					
SR-F05	60Hz-18kHz			25cm, Compression Driver (90°H x 40°V) CD Horn	99dB	Epoxy Paint Black		Acrylic Paint Black	Neutrik NL4MP × 2 and Screw Terminal	Medium Density Fiberboard Cabinet	
SR-M05L/R											
SR-M3L/R									600W	65Hz-20kHz	38cm, Cone Speaker (60°H x 40°V) CD Horn w/Compression Driver
SR-M1	360W(Low) 240W(High)	8Ω (low) 16 Ω(high)	70Hz-20kHz (AC-M1's use)	30cm, Compression Driver (90°H x 40°V) CD Horn	99dB	Epoxy Paint Black (APITON Plywood Cabinet)		Acrylic Paint Black	Bi-amp. Driver with Electronic Control Unit (AC-M1)		
SR-M2	720W(Low) 240W(High)		45Hz-20kHz (AC-M1's use)	Two 30cm, Compression Driver (90°H x 40°V) CD Horn	102dB						

• ES Series

ES-0851	2-Way Bass Reflex	600W	8Ω	80Hz-20kHz	25cm Cone Speaker 90°H and 60°V (60°H x 90°V)CD Horn w/Compression Driver	97dB		Plywood, black, urethane paint	Steel plate, black, acrylic paint	Neutrik NL4MP x 2, M5 screw	
ES-0871				70Hz-20kHz	38cm Cone Speaker 90°H and 60°V (60°H x 90°V)CD Horn w/Compression Driver	100dB					
ES-C0651	Sealed	180W		80Hz-20kHz	2-Way Coaxial Unit, 25cm Woofer, CD Horn w/Compression Driver(60°H x 60°V)	96dB		Wood, Black	Rolled steel plate, white (option, FG- C0651)	Push Terminals	Option, MT-S0601 Matching Transformer
ES-0422		240W		120Hz-20kHz	Two 12cm Woofers, CD Horn w/Compression Driver(100°H x 50°V)	91dB		Wood Urethane Paint, White	Steel Plate Acrylic Paint, White	M5 Screw Terminal	
ES-0424					Four 12cm Woofers, CD Horn w/Compression Driver(100°H x 50°V)	95dB					
ES-0426					360W	Six 12cm Woofers, CD Horn w/Compression Driver(100°H x 50°V)					
ES-0422WP	Sealed/Weather- Resistant	240W			Two 12cm Woofers, CD Horn w/Compression Driver(100°H x 50°V)	91dB		Wood FRP Coating Paint, White	Stainless Steel Paint, White		
ES-0424WP		360W			Four 12cm Woofers, CD Horn w/Compression Driver(100°H x 50°V)	95dB					
ES-0426WP					Six 12cm Woofers, CD Horn w/Compression Driver(100°H x 50°V)	96dB					

• T Series Speakers

T-650	Bass Reflex	360W	8Ω	80Hz-20kHz	Two 25cm Woofers, Two CD Horns w/Compression Driver	100dB		Coniferous Plywood, Urethane Paint, Black	Steel Plate Acrylic Paint, Black	M5 Screw Terminal	Option: MT-S0601 Matching Transformer
T-550	Sealed	180W		100Hz-20kHz	2-Way Coaxial Unit, 25cm Woofer, CD Horn w/Compression Driver	96dB					

• H Series Speakers

H-1	2-Way Bass- Reflex/ Foreground	12W*	4Ω, 16Ω, 100V: 830Ω, 1.7kΩ, 3.3kΩ 70V: 420Ω, 830Ω, 1.7kΩ, 3.3kΩ	120Hz-20kHz	8 x 5cm Woofer, Balanced Dome Tweeter	85dB		Fire- Resistant	Rolled Steel Plate, White	Detachable Screw Terminal, 2 each +/-		
H-2					100Hz-20kHz	10cm Woofer, Balanced Dome Tweeter		88dB	ABS Resin, White			Steel Plate, Off-White
H-2WP									ABS Resin, White			Stainless Steel Off-White
H-3		30W*	8Ω, 16Ω, 100V: 330Ω, 670kΩ, 1.3kΩ 70V: 170Ω, 330Ω, 670Ω, 1.3kΩ	100Hz-20kHz	10cm Woofer x 2, 2.5cm Dome Tweeter	89dB		Fire- Resistant	Steel Plate, Off-White			
H-3WP								ABS Resin, Off-White	Stainless Steel Off-White			
HB-1	Subwoofer	240W	8Ω	45Hz-200Hz	20cm Cone	91dB		Steel plate, Off-White	Punched Net, Off-White			

Notes: *: Rated Input

Model	Type	Continuous Power Input	Input Impedance	Freq. Response	Speaker Component	Efficiency (SPL)	Attenuators (Max. cut)	Finish	Grille	Connectors (incl. In/Out)	Other Features	
• F Series Speakers												
F-101C	Bass Reflex/ Distributed FGM	120W	8Ω	80Hz-18kHz	12cm Full-Range Cone Speaker	90dB		Black	Punched Steel, White	Hardwire	Optional X-former, Overload Protected	
F-101CM		20W*	100V: 500Ω, 1kΩ, 2kΩ, 3.3kΩ 10kΩ 70V: 500Ω, 1kΩ 1.7kΩ, 5kΩ								Built-in Matching Transformer	
F-121C		120W	8Ω								Optional X-former, Overload Protected, used with AC-120	
F-121CM		20W*	100V: 500Ω, 1kΩ, 2kΩ, 3.3kΩ 10kΩ 70V: 500Ω, 1kΩ 1.7kΩ, 5kΩ								Built-in Matching Transformer, used with AC-120	
F-10B/W	Sealed/ Foreground	45W	8Ω	100Hz-18kHz	10cm Full-Range Speaker in Triangular Corner Enclosure	88dB		Black/White Triangle	Removable Matching Color Jersey		Optional X-former	
F-10BM/ F-10WM		5W*	100V: 3.3kΩ 2kΩ 70V: 1.7kΩ, 1kΩ								Built-in Matching Transformer	
F-160G/W	2-Way Bass Reflex/Foreground	150W	8Ω	100Hz-20kHz	13cm Woofer, 3cm Dome Tweeter	91dB		Gray (F-160G/ F-160GM) White (F-160W/ F-160WM)	Punched Metal, Gray (F-160G/ F-160GM) White (F-160W/ F-160WM)	Push Terminals, 2-1/4" Jacks		
F-160GM/ F-160WM	2-Way Bass Reflex	30W*	100V: 330Ω 500Ω, 1kΩ, 2kΩ 70V: 170Ω, 330Ω 500Ω, 1kΩ 2kΩ								Built-in Matching Transformer	
F-240G/W	2-Way Bass Reflex/Foreground	150W	8Ω	65Hz-20kHz	16cm Woofer, 3cm Dome Tweeter	92dB		Gray (F-240G/ F-240GM) White (F-240W/ F-240WM)	Punched Metal, Gray (F-240G/ F-240GM) White (F-240W/ F-240WM)			
F-240GM/ F-240WM	2-Way Bass Reflex	30W*	100V: 330Ω 500Ω, 1kΩ, 2kΩ 70V: 170Ω, 330Ω 500Ω, 1kΩ 2kΩ							Built-in Matching Transformer		
F-500SR	2-Way Bass Reflex	240W	8Ω	70Hz-20kHz	20cm LF Driver, Comp. HF Driver 60°H x 40°V CD Horn	93dB	1HF (15dB)	Polyprop., Gray	Punching Net	Push Terminals 2-1/4" Jacks convertible to XLR	CD Horn mountable horiz. or vert., Overload Protected, Plastic Cabinet	
F-505W				65Hz-20kHz	30cm LF Driver, Comp. HF Driver 60°H x 40°V CD Horn	98dB			Punched for LF, Jersey Grille for HF			
F-601SR		360W	Punching Net									
F-333/ F-333G	2-Way Bass Reflex/Foreground	180W	8Ω	70Hz-20kHz	13cm Woofer, CD Horn with Piezo Driver	90dB		Light Gray (F333/333M) Dark Gray (F333G/ 333GM)	Punched Metal, Grayish Gold	Push Terminals		
F-333M/ F-333MG	2-Way Bass Reflex	30W*	100V: 330Ω 500Ω, 1kΩ, 2kΩ 70V: 170Ω, 330Ω 500Ω, 1kΩ 2kΩ								Built-in Matching Transformer	
F-777		240W	8Ω	60Hz-20kHz	20cm Woofer, CD Horn with Compression Driver	93dB		Polypropylene Resin Light Gray	Punched Metal, Black			
FB-10	Subwoofer for F-10 Series	60W		40Hz-100kHz	16cm Subwoofer Speaker in Designer Enclosure	83dB		Black Poly				
FB-100	Acoustic Super Woofer	450W		35Hz-160kHz	25cm Cone Speaker	94 (88dB)	MDF, Black		Detachable Screw Terminals 2 each +/-			
F-160WP	2-Way Bass Reflex/Weather-Resistant	30W*	100V: 330Ω 500Ω, 1kΩ, 2kΩ 70V: 170Ω, 330Ω 500Ω, 1kΩ 2kΩ	100Hz-20kHz	13cm Woofer, 3cm Dome Tweeter	91dB		Polyprop. Gray	Punched Metal, Gray			
F-505WP	2-Way Sealed/Weather-Resistant	60W*	83Ω 170Ω 330Ω 670Ω	80Hz-20kHz	20cm, Compression HF Driver w/ 60°H x 40°V CD Horn	93dB		Polyprop. resin, Ivory	Stainless Steel, Ivory	Pigtail Cable	Overload Protected, Weather-Resistant Cabinet w/Handle	
F-505WP-L		240W	8Ω									
F-605WP		120W*	42Ω 83Ω 170Ω 330Ω		30cm, Compression HF Driver w/ 60°H x 40°V CD Horn							
F-605WP-L		360W	8Ω									

Notes: * : Rated Input

Model	Type	Continuous Power Input	Input Impedance	Freq. Response	Speaker Component	Efficiency (SPL)	Attenuators (Max. cut)	Finish	Grille	Connectors (incl. In/Out)	Other Features
-------	------	------------------------	-----------------	----------------	-------------------	------------------	------------------------	--------	--------	---------------------------	----------------

• SL Series Speakers

SL-122	Sealed	240W	8Ω	70Hz-20kHz	30cm Woofer, Decoupled Piezo Tweeter, 90°H x 40°V CD Horn	95dB		Gray Leatherette	Punched Metal Grille, Black	Two Parallel 1/4" Jacks In/Out	Interlock Corners for stacking, Carrying Strap
SL-152						98dB					
SL-222	Sealed Twin Woofers			50Hz-20kHz	30cm Wooferx2, Decoupled Piezo Tweeter, 90°H x 40°V CD Horn	96dB					Carrying Strap
SL-122M	Sealed Floor Monitor				70Hz-20kHz	30cm Woofer, Decoupled Piezo Tweeter, 90°H x 40°V CD Horn					
SL-152M				38cm Woofer, Decoupled Piezo Tweeter, 90°H x 40°V CD Horn		98dB					
SL-60W	2-Way Sealed/Weather- Resistant			240W	50Hz-20kHz	30cm Woofer, Piezo Driver, 90°Hx40°V CD Horn					92dB
SL-60WH		80W*	100V: 125Ω 250Ω 330Ω 500Ω 1kΩ								

• SM Series Speakers

SM-60	Sealed	210W	8Ω	110Hz-16kHz	Two 12cm Full-Range Drivers	90dB		Cast Aluminum, Black	Punched Metal, Black	Two Locking Parallel 1/4" Jacks	160Ω Bridge Out Jack
SM-68					1 atten. (40dB)		Bridge Out Jack				
SM-75		25W		110Hz-20kHz	Two 12cm Full-Range Drivers, 4.7cm Cone Tweeter	N/A	XLR 1/4"			2CH Mixer, Tone, Headphone Amp.	
SM-25M					Two 12cm Full-Range Drivers, 5cm Cone Tweeter, 25W Power Amp. Line In, Bridge Out						

• Personal Monitors

280-ME-AV	Sealed	90W	8Ω	60Hz-20kHz	20cm Woofer, 3cm Soft Dome Mid, 2cm Poly Dome Tweeter	89dB	1-MID (10dB)	Matted Gray Vinyl Chloride Coating	Removable Black Cloth Grille	Push-Type Terminals	Very Flat Frequency Response for studio reference use, symmetrical pairs for imaging, all models A/V shielded
RS-21M		100W		100Hz-17kHz	12cm Full-Range Cone Driver	88dB		Black Tolex	Jersey, Black		Lightweight

• Paging Horn Speakers

SC-610	Reflex, Indoor/Outdoor Use	10W*	8Ω	315Hz- 12.5kHz	172 x 126 Reflex Horn with Driver	110dB		Aluminum, Off-White		Terminal	
SC-610M			100V: 1kΩ, 2kΩ, 3.3kΩ, 10kΩ 70V: 500Ω, 1kΩ, 2kΩ, 3.3kΩ, 10kΩ								Built-in Transformer
SC-615		15W*	8Ω	280Hz- 12.5kHz	222 x 162 Reflex Horn with Driver	112dB					
SC-615M			100V: 670Ω, 1kΩ, 2kΩ, 3.3kΩ 70V: 330Ω, 670Ω, 1kΩ, 2kΩ, 3.3kΩ								Built-in Transformer
SC-630		30W*	8Ω	250Hz- 10kHz	285 x 205 Reflex Horn with Driver	113dB					
SC-630M			100V: 330Ω, 670Ω, 1kΩ, 2kΩ 70V: 170Ω, 330Ω, 670Ω, 1kΩ, 2kΩ								Built-in Transformer

• Reflex Horn Speakers

TC-615	Reflex, Indoor/Outdoor Use	15W*	8Ω	250Hz-7kHz	ø400mm Reflex Horn with Driver	108dB		Aluminum, Off-White		Terminal	
TC-615M			100V: 670Ω, 1kΩ, 2kΩ, 3.3kΩ 70V: 330Ω, 670Ω, 1kΩ, 2kΩ, 3.3kΩ								Built-in Transformer
TC-630		30W*	16Ω	200Hz-6kHz	ø500mm Reflex Horn with Driver	110dB					
TC-630M			100V: 330Ω, 670Ω, 1kΩ, 2kΩ, 70V: 170Ω, 330Ω, 670Ω, 1kΩ, 2kΩ								Built-in Transformer

• Mobile Mounted Speakers

TC-10P	Reflex/Mobile Mount	10W	8Ω	400Hz-5.5kHz	ø130mm Reflex Horn with Driver	101dB		Cream		Terminal	B-2, B-9 (Brackets)
TC-35P		35W		250Hz-8kHz	ø166mm Reflex Horn with Driver	104dB		White			B-2 (Brackets)
SC-650		50W*	16Ω	250Hz-6kHz	403 x 297.5mm Reflex Horn with Driver	109dB		Aluminum, Off-White			B-8 (Brackets)

* Mobile mount use: 30W

• Ultra-High Power Speaker

SC-240	Ultra-High Power	240W	8Ωx4	250Hz-5kHz	60W x 4	107dB		Aluminum, Ivory		Terminal	
--------	------------------	------	------	------------	---------	-------	--	-----------------	--	----------	--

• Explosion-Proof Horn Speakers

TP-M15E	Reflex/Explosion Proof	15W*	670Ω, 1kΩ, 2kΩ	350Hz-5.5kHz	Ø397mm Reflex Horn Explosion Proof with Driver	105dB		Aluminum, Ivory		Terminal	Built-in Transformer
TP-M15D				350Hz-4.5kHz	Ø242mm Reflex Horn Explosion Proof with Driver	104dB					

Notes: *: Rated Input

Model	Type	Continuous Power Input	Input Impedance	Freq. Response	Speaker Component	Efficiency (SPL)	Attenuators (Max. cut)	Finish	Grille	Connectors (incl. In/Out)	Other Features
-------	------	------------------------	-----------------	----------------	-------------------	------------------	------------------------	--------	--------	---------------------------	----------------

• Bi-Directional Box Speakers

BS-61WA	Bi-Directional Box Type	6W	1.7kΩ, 5kΩ	130Hz-13kHz	16cm Full-Range Dynamic Cone	92dB		Wood, Off-White	Cloth Off-White	Terminal	YS-31W (Mounting Bracket)
BS-61WT-A							○				

• Wall-Mounting Box Speakers

BS-330	Wall-Mounting Box Speaker	3W*	3.3kΩ, 10kΩ	220Hz- 14KHz	12cm Full-Range Dynamic Cone	91dB		ABS Resin	Off-White	Terminal		
BS-330T							○					
BS-677BT		6W*	1.7kΩ	100Hz- 10kHz	12cm Full-Range Dynamic Cone		○	Vinyl Chloride Particle Board	Black			
BS-677WT							○		White			
BS-677B									Black			
BS-677W									White			
BS-102SA		10W*	1kΩ, 2kΩ	100Hz- 13kHz	20cm Full-Range Dynamic Cone	94dB		Wood, Off-White	Cloth Off-White			YS-32S (Mounting Bracket)
BS-102ST-A							○					

• Universal Speakers

BS-1030B	2-Way Bass Reflex	30W*	8Ω 100V: 30Ω (30W), 500Ω (20W), 670Ω (15W), 1kΩ (10W), 2kΩ (5W) 70V: 170Ω (30W), 250Ω (20W), 330Ω (15W), 500Ω (10W), 1kΩ (5W)	80Hz-20kHz	12cm Dynamic Cone 2.5cm Balanced Dome Tweeter	90dB		ABS Resin, Black, Paint	Punching Net, Black	Terminal	
BS-1030W								ABS Resin, White, Paint			
BS-1110W	Full-Range Bass Reflex	10W*	100V: 1kΩ (10W), 2kΩ (5W) 70V: 500Ω (10W), 1kΩ (5W), 4Ω (10W)	150Hz-14kHz	12cm Dynamic Cone x 2	92dB		Plywood Vinyl Coating, White	Punching Net, White	Push-In Type	
BS-1120W	2-Way Bass Reflex	20W*	100V: 500Ω (20W), 1kΩ (10W) 70V: 250Ω (20W), 500Ω (10W), 8Ω (20W)	150Hz-20kHz	12cm Dynamic Cone x 4 Balanced Dome Tweeter	95dB					

• Box-Type Splashproof Speakers

BS-5W	Box-Type Splashproof Speaker	5W*	2kΩ, 3.3kΩ, 5kΩ	120Hz-18kHz	10cm Full-Range Dynamic Cone	90dB		Polyprop. Gray	Aluminum Gray	Terminal	Any color available with min. 100pc. order	
BS-10WL		10W*	8Ω			88dB						
BS-20W		20W*	500Ω, 670Ω, 1kΩ 2kΩ		100Hz-20kHz	Mid/Low: 13cm Splashproof Cone, High: CD Horn plus Splashproof Piezo Driver		94dB	ABS Resin, Black/White			Punching Net, Black/White
BS-20W-WHT												

• Firedome Speaker

PC-39F	Fire-Resistant Flush-Mount Ceiling	3W*	3.3kΩ, 5kΩ, 10kΩ	300Hz-12kHz	16cm Dynamic Cone	96dB		Metallic, Off-White	Metallic, Off-White	Connector	
--------	------------------------------------	-----	------------------	-------------	-------------------	------	--	---------------------	---------------------	-----------	--

• Heat-Resistant Ceiling Horn Speakers

PC-129	Heat-Resistant/Ceiling Mount	1W*	10kΩ	500Hz-8kHz	Horn Speaker, ø116 x 130(D)mm	100dB		Aluminum, Off-White		Connector	Withstands 380°C Air Current for 15 mins.
PC-139				500Hz-10kHz	Horn Speaker, ø122 x 146(D)mm						

• FGM Ceiling Speaker

PC-212	Distributed FGM	15W*	100V: 670Ω, 1kΩ, 2kΩ 70V: 670Ω, 1kΩ, 2kΩ	50Hz-18kHz	20cm Coaxial 2-Way Ceiling Cone	91dB		Aluminum	Aluminum Punched Net, Silver	Terminal	
--------	-----------------	------	---	------------	---------------------------------	------	--	----------	------------------------------	----------	--

• Flush-Mounting Type Ceiling Speakers

Screw-in Type

PC-645R	Panel Cone Speaker	100V: 6W* 70V: 3W*	1.7kΩ, 3.3kΩ, 6.7kΩ, 13kΩ	100Hz-12kHz	12cm Dynamic Cone	90dB		ABS Resin, Off-White	Aluminum Lath, Off-White	Terminal	
PC-643S											
PC-646R											
PC-644S											

Spring Catch Type

PC-1864	Panel Cone Speaker	100V: 6W* 70V: 3W*	1.7kΩ, 3.3kΩ, 6.7kΩ, 13kΩ	100Hz-16kHz	12cm Dynamic Cone	90dB		ABS Resin, Off-White	Steel Net, Off-White	Terminal	YS-270 (Protection Cover)
PC-1863								Aluminum Off-White			
PC-1867											

Separate Type

CM-760	Separate Type	6W*	1.7kΩ, 3.3kΩ, 6.7kΩ, 13kΩ	100Hz-16kHz	12cm Full-Range Dynamic Cone	90dB			Resom, Black	Terminal	Optional Speaker Grille: PC-73: Baffle: ABS Resin, Off-White/ Baffle: ABS Resin, Off-White/ Grille: Aluminum Net, Off-White/ PC-77: Baffle, Metal Off-White/ Grille: Aluminum Net, Off-White Terminal
CM-960					16cm Full-Range Dynamic Cone	92dB					Optional Speaker Grille: PC-93: Baffle: ABS Resin, Off-White/ Baffle: ABS Resin, Off-White/ Grille: Aluminum Net, Off-White/ PC-97: Baffle, Metal Off-White/ Grille: Aluminum Net, Off-White

Notes: *: Rated Input

Model	Type	Continuous Power Input	Input Impedance	Freq. Response	Speaker Component	Efficiency (SPL)	Attenuators (Max. cut)	Finish	Grille	Connectors (incl. In/Out)	Other Features
-------	------	------------------------	-----------------	----------------	-------------------	------------------	------------------------	--------	--------	---------------------------	----------------

• Surface-Mounting Type Ceiling Speaker

PC-2668	18cm Baffle Type	100V: 6W* 70V: 3W*	1.7kΩ 3.3kΩ 6.7kΩ 13kΩ	100Hz-16kHz	12cm Dynamic Cone	86dB		ABS Resin, Off-White		Terminal	
---------	------------------	-----------------------	---------------------------	-------------	-------------------	------	--	-------------------------	--	----------	--

• Splashproof Ceiling Speakers

PC-3CL	Ceiling Flush-Mount	3W*	3.3kΩ	150Hz-20kHz	8cm Splashproof Dynamic Cone	87dB		ABS Resin, Off-White	Stainless Steel Punched Net	Terminal	Shower Room & Indoor Pool, Bathroom, Steam Sauna
PC-3WR				180Hz-20kHz		88dB		ABS Resin, Chrome-Plated			

• Column Speakers

TZ-105	Metal Case Type	10W*	1kΩ, 2kΩ	150Hz-10kHz	12cm x 2 Dynamic Cone	90dB		Extruded Aluminum, Silver Gray	Punched Net, Black	Terminal	YS-301 (Outdoor-Use Mounting Bracket) ST-490 (Speaker Stand)
TZ-205		20W*	500Ω, 1kΩ		12cm x 4 Dynamic Cone	93dB					
TZ-301		30W*	330Ω, 670Ω	160Hz-10kHz	12.7 x 17.8cm Oval Shape Dynamic Conex6	100dB					

• Wide Range Weatherproof Speakers

CS-64	Wide Range/ Weatherproof	6W*	100V: 1.7kΩ, 3.3kΩ, 10kΩ 70V: 830Ω, 1.7kΩ, 3.3kΩ, 10kΩ	130Hz-13kHz	12cm Dynamic Cone	96dB		ABS Resin, Off-White	Punched Steel Plate, Dark Gray	Terminal	
CS-154		15W*	100V: 670Ω, 1kΩ, 2kΩ 70V: 330Ω, 620kΩ, 1kΩ, 2kΩ	150Hz-15kHz		97dB			Aluminum Net, Gray		
CS-304		30W*	100V: 330Ω, 500Ω, 1kΩ 70V: 170Ω, 330Ω, 500Ω, 1kΩ	120Hz-15kHz		98dB					

• Pendent Speakers

PE-84	Pendent Type	8W*	310Ω, 625Ω, 1.25kΩ, 2.5kΩ, 5kΩ	160Hz-20kHz	16cm Dynamic Cone	99dB		Cover gray, Case ivory		Terminal	
PE-164		16W*	155Ω, 310Ω,625Ω, 1.25kΩ, 2.5kΩ			101dB					

• Pendent Ball Speakers

PE-63B	Pendent Ball Type	6W*	100V: 1.7kΩ, 3.3kΩ 6.7kΩ 70V: 830Ω, 1.7kΩ 3.3kΩ 6.7kΩ	150Hz-10kHz	12cm Dynamic Cone	87dB		Black		Terminal	
PE-63W			Off-White								
PE-123B		12W*	100V: 830Ω, 1.7kΩ 3.3kΩ 70V: 420kΩ 830Ω, 1.7kΩ 3.3kΩ					Black			
PE-123W			Off-White								

• Lamp Speakers

LS-300B	Lamp/Spotlight Type	3W*	3.3kΩ 10kΩ	300Hz-16kHz	7.7cm Dynamic Cone	86dB		Black	Black	Terminal	
LS-300W								Ivory	Gray		
LS-500B		5W*	2kΩ 3.3kΩ	200Hz-20kHz		85dB		Black	Black		
LS-500W								Ivory	Gray		
LS-10		10W*	16Ω	150Hz-18kHz		83dB		ABS Resin			

• Corner Speakers

PS-16BM	Full-Range Bass Reflex Type	10W*	1kΩ (10W), 2kΩ (5W), 3.3kΩ (3W), 8Ω (low impedance connection)	125Hz-18kHz	10cm Cone Woofer	89dB		Wood, Polyurethane Paint, Black	Punched Steel Sheet, Acrylic Paint, Black	Terminal							
PS-16WM				100Hz-20kHz	10cm Cone Woofer, 2cm Film Tweeter	90dB		Wood, Polyurethane Paint, White	Punched Steel Sheet, Acrylic Paint, White								
PS-32BM	2-Way Bass Reflex Type							Wood, Polyurethane Paint, Black	Punched Steel Sheet, Acrylic Paint, Black								
PS-32WM								Wood, Polyurethane Paint, White	Punched Steel Sheet, Acrylic Paint, White								

• Projection Speakers

PJ-100W	Reflex/ Wide Range	10W*	50V: 250Ω, 500Ω, 1kΩ, 2kΩ, 4kΩ 70V: 500Ω, 1kΩ, 2kΩ, 4kΩ 100V: 1kΩ, 2kΩ, 4kΩ	65Hz-15kHz	12cm Dynamic Cone	92dB		ABS Resin, Off-White		Terminal	Built-in Transformer (50/70/100V Lines)
PJ-200W		20W*	50V: 125Ω, 250Ω, 1kΩ, 2kΩ, 70V: 250Ω, 500Ω, 1kΩ, 2kΩ 100V: 500Ω, 1kΩ, 2kΩ	50Hz-20kHz	16cm Dynamic Cone	95dB					

• Wall Flush-Mount Speakers

PC-391	Wall Flush-Mount	3W*	3.3kΩ	150Hz-15kHz	7.7cm Dynamic Cone	86dB		Stainless Steel, Silver		Terminal	
PCC-391T							○				

Notes: *: Rated Input