

SPECIFICATIONS

CUSTOMER	Radio Parts	CUSTOMER MODEL NO.	GDG-CX61M	OUR MODEL NO.	
DESCRIPTION	61/2" MAGNETIC CEILING SPEAKER				
NO.	ITEM	SPECIFICATION	TEST CONDITION		
1	SPKR SPECIFICATION	WOOFER: 6.5" BLACK PP. CONE/RUBBER GDGE TWEETER: Φ13 MYLAR	AMBIENT TEMPERTURE: 15~35°C RELATIVE HUMDIDTY: 25%~75% PRESSURE: 86kPa~106kPa		
2	Transformer	-----	-----		
3	RATED IMPEDANCE	8Ω ±15%	AT 1 W, 300 Hz		
4	BUZZES & RATTLES	MUST BE NORMAL #	SINE WAVE 8.9V, AT 60-18KHz		
5	RESONANT FREQ. (F0)	75Hz ± 20%	WITHOUT BAFFLE		
6	SENSITIVITY (OUTPUT S. P. L)	87±3dB 1M/1W	100. 200. 400. 800. 1. 6K. 3. 2K. 6. 4K 12. 8KHz The 8 point average		
7	ACROSS FREQUENCY	-----	-----		
8	RATED FREQ. RESP.	F0~18KHz	-15dB		
9	RATED NOISE POWER	25 WATTS	IEC265-5		
10	RATED LONG-TERM MAX. POWER	50 WATTS	IEC265-5		
11	LOAD TEST	-----	IEC265-5		
12	HEAT TEST	-----	IEC265-5		
13	LOW TEMPERATURE TEST	-----	IEC265-5		
14	DISTORTION	-----	RATED POWER INPUT, AT 1K Hz.		
15	POLARITY	-----	APPLY POSITIVE D. C TO THE TERMINAL MARKED (+)		
16	WEIGHT	1. 5Kg	APPROVED BY		
17	sound Load	290 L standard test box	APPROVED BY	黎文春	
18	DIMENSIONS	Φ233*H92 mm	DESIGNED BY	赖小康	
19	INSTALLATION HOLE SIZE	Φ206*H88 mm	DATE	2016/7/21	