
IX SERIES 2 Peer-to-Peer IP Video Intercom

ZAIPHONE®



IX-DVF-P

IP Card Access

Same features

as IX-DVF, plus:

HID[®] multiCLASS

Reader (requires a

3rd-party host and additional wire to

power card reader)

SE® Proximity Card

Video Door Station

 Hands-free communication • SIP compatible with handset for privacy touchscreen

- · Compatible slot
- Camera for 2-way video calls

IP Video Door Station

PoE (with passthrough

port) or 24V DC

SIP compatible

Compatible slot

Fixed camera

die cast cover

vandal resistant

IX-DVF-4

• 4 call buttons

Surface mount

Weather and

• Aluminum

for microSD[™] card

• 7"LCD

8 speed-dial

IX-DV

buttons

Door Stations

.

- for microSD[™] card Wall or desk mount (stand included)

0



- SIP compatible communication Compatible slot • 7" LCD
- for microSD[™] card touchscreen Wall or desk mount 8 speed-dial (stand included) buttons
- Camera for 2-way video calls

- PoE
- 3-1/2" LCD screen
- 6 speed-dial buttons
- Hands-free communication with
- handset for privacy Wall or desk mount (stand included)

IX-DA

IP Video

PoE

Fixed

camera

chassis

Weather

• Surface

resistant

Plastic

Door Station

for Smartphones and Tablets (requires 1 master station and 1 IXW-MA per 8 apps in the system mobile devices not included)

- · Provides station functionality to answer calls and unlock doors
- 4 speed-dial buttons can be programmed to call, page, or monitor
- Available on Google Play™ (Google Play is a trademark of Google LLC.)
- Available on the App StoreSM (App Store is a service mark of Apple Inc.)





• PoE

- SIP compatible
- Door release button · Internal communication
- with other sub stations
- Hands-free communication with handset for privacy
- Wall mount



- Door Station
- PoE
- Plastic chassis · Weather resistant
- Surface mount



IP Video Door Station • Fixed camera Stainless steel panel · Weather resistant

IX-DVF

IP Video Door Station

• PoE (with passthrough

port) or 24V DC

SIP compatible

· Compatible slot

· Fixed camera

for microSD[™] card

- Flush mount
- (back box included)

· Stainless steel panel • Weather and vandal resistant

- Flush mount (back box included)
 - IX-SS-2G IP Audio 0
 - Door Station • PoE
 - SIP compatible
 - Stainless steel panel
 - · Weather and vandal resistant
 - Flush mount (fits 2-gang box)
- mount **IX-SSA** IP Audio
- PoE (with
 - Door Station passthrough port) or 24V DC SIP compatible
- steel panel Weather and Flush mount

Stainless

Compatible slot for microSD[™] card



IX SERIES 2 Peer-to-Peer IP Video Intercom

IPW-1VC

• PoE

IX-10AS

PoE (x10)

2-Wire Network Adaptor

to an IP video intercom

• Upgrade 2-wire analog systems

Use existing wire — up to 1,000' (18-22AWG shielded, unshielded)

Compact design is small enough to

fit behind most door or sub stations

2-Wire Audio Door/Sub Station Network

Easily Upgrade LE or

Network Adaptors

NE Series Stations with

Audio Door/Sub Station

IX-MB

Adaptor (includes 10 IX-1AS adaptors

each requires a network connection) Supports up to 10 LE Series, NE Series, or 8Ω Door/Sub Stations

(includes power supply)

Components & Accessories

Emergency Stations



IX-DVF-2RA/IX-DVF-RA

ADA Compliant IP Video Emergency Station (IX-DVF-2RA has two call buttons, IX-DVF-RA has one call button)

- PoE (with passthrough Lettering and port) or 24V DC braille signage
- SIP compatible
- Compatible slot for microSD[™] card
- Fixed camera
- Stainless steel panel • Weather and
 - vandal resistant

LED call status indicator

• 2 Form C relay outputs

Emergency Wall Boxes & Towers



WB-CA/WB-HA

- ADA Compliant Wall Box • Cage (WB-CA) or hood (WB-HA) with
- beacon/strobe light ASSISTANCE lettering
- UL Listed electrical box
- Stainless steel enclosure with slim, 4" depth
- Wall mount

Modular Towers

Mid-Level Single-Station, High-Level Dual-Station, and High-Level Single-Station Towers

- · UL Listed electrical box
- · CCTV camera arm module with universal pipe threading
- Includes accessory mounting hardware
- Large, easy-access panel on each module
- Modular design provides lower freight costs and easier assembly than non-modular towers
- Variety of configurations. including size, lettering, and colors
- Zinc-treated steel with powder coating
- For more information visit aiphone.com/IX2Sheet



WB-CE/WB-HE

Cage (WB-CE) or

hood (WB-HÉ) with

beacon/strobe light

EMERGENCY lettering

• UL Listed electrical box

with slim, 4" depth

• Wall mount

Stainless steel enclosure

PS-POE

eliminating the

power supply

wire - only one

cable is needed

from the PoE+

switch when wired

with an IX Series 2

Avoid added

ADA Compliant Wall Box



IX-SSA-2RA/IX-SSA-RA

ADA Compliant IP Audio Emergency Station (IX-SSA-2RA has two call buttons, IX-SSA-RA has one call button)

EMERGENCY

- PoE (with passthrough LED call port) or 24V DC status indicator • SIP compatible • 2 Form C relay outputs
- Compatible slot for microSD[™] card Stainless steel panel Lettering and Weather and braille signage
 - vandal resistant

(TWS-Z4, TWS-Z2, and TWS-Z1 will be available Nov 2019)

TWS-Z4

Zone 4 Solar Tower Set

Includes WB-HE

Surveillance's

and mounting

Wireless solar

solution powers

components

solar panel

wall box with Sun



Adaptors

IXW-MA IP Relay Adaptor

- · Compatibility with IX Support Tool makes programming efficient - no need to program adaptors separately
- PoF
- 10 outputs
- Supports up to 8 mobile apps



- Network Paging Adaptor
- 8Ω, 5W speaker output
- 600Ω amplifier output
- · Audio input
- PoE



- 2-Wire Audio Door/Sub
- Station Network Adaptor Supports 1 LE Series, NE Series, or 8Ω Door/Sub Station
- PoE

Box for

IX-DA





KAW-D 30° Angle 45° Mullion Mounting IX-BA or Bracket for IX-BA or IX-DA





Mullion Mounting Bracket for IX-DV (available Card Reader for Nov 2019)





SBX-IDVF SBX-IDVFRA Surface

Mount Box for IX-DVF-2RA, IX-DVF-RA, IX-DVF-P. IX-DVF-4 IX-SSA-2RA or IX-SSA-RA



TW-MKL

L-Bolt Mounting Kit for Modular Towers (an I-bolt mounting kit is required for tower installation - TW-MKL is recommended)



TWS-Z1 (not shown)

- Same as TWS-Z4, but equipped with three solar panels for
- emergency station Mounts directly to the back of an IX Series 2 emergency call station or 1-gang box
- Can withstand temperatures ranging
- from -40 to 167° F

PoE Splitter

 Powers strobe light, need of a separate

K

two solar panels for sun-rated zones 2.0-3.9

Zone 1 Solar Tower Set

- sun-rated zones 1.0-1.9

TW-SPL

Tower Mounting Plate for IX-DVF or IX-SSA (adapts standard door station to an Aiphone tower or wall box)

SBX-IXDV30

30° Angle

Box for IX-DV

SBX-2G/A Surface Mount Box for IX-SS-2G







(adapts emergency station to an existing Code Blue® or Talk-A-Phone®





Code Blue® is a registered trademark of Code Blue Corporation. Talk-A-Phone® is registered trademark of Talkaphone LLC.

Surface Mount Box for IX-DVF or IX-SSA MB-RF1 Retrofit





or IX-SSA-RA