

HDMIAW

HDMI EXTENDER OVER ANY WIRE

EXTENDING UP TO 3.8KM

TRANSMITTER + RECEIVER



HDMIAW can extend your HDMI source over any 2-conductor cable including twisted cable, telephone cable or CAT5/6 etc. It is an ideal HDMI extender over your existing cable.

- ✓ With 1x Loop HDMI output at transmitter
- Transmit HDMI signal up to 3.8 Km
- Supports Multi-level cascading
- → HDMI resolution up to 1080p
- → HDCP compliant
- → IR pass-through control

SPECIFICATIONS

Operating Temperature Range	-5 to 35°C
Operating Humidity Range	5 to 90%RH (No condensation)
Compression Rate	H.264 compression
Bit Rate	15Mbps
Latency	From TX to RX is about 200ms to 450ms
Supported Audio Format	LPCM audio format
Transmission Distance	3800m via 2-conductor cable; NOTE: This distance is tested on 18AWG UL2468, stranded 2 core cable. Longer distances could be achieved with greater quality cables
Supported Video Format	DTV/HDTV: 480i/ 480p/ 576i/ 576p/ 720p/ 1080i/ 1080p
	VESA: 800x600, 1024x768, 1280x768, 1280x960, 1280x1024
	VESA: 800x600, 1024x768, 1280x768, 1280x960, 1280x1024
Connections on TX	1x HDMI input, 1x HDMI loop out, IR-TX socket, 2x terminal post, power supply socket
Connections on RX	2x terminal post, 1x HDMI output, IR-RX socket, power supply socket
Power Consumption	TX: 6.5 Watts, RX: 5.5 Watts
Dimension	206.2(L)x 110(W)x 33(H)mm
IR Frequency	38K- 56KHz



MODEL: HDMIAW CODE: 64510347 WARRANTY: 1 YEAR





INCLUDES

- [↑] 1x Transmitter
- → 1x Receiver
- 2x Power Adapters DC 12V 2A
- → 8x Screws
- 4x Detachable Mounting Ears
- [↑] 1x IR TX Cable
- → 1x IR RX Cable
- Users Manual

PLEASE NOTE:

This product can not be connected to 220V/380V high voltage.



HDMIAW

HDMI EXTENDER OVER ANY WIRE

EXTENDING UP TO 3.8KM

TRANSMITTER + RECEIVER

